

- 1.) H.-M. Rein: "Der Umschaltvorgang bei Transistor-Kippstufen – Die astabile Kippstufe", AEÜ 19 (1965), pp. 411-423.
- 2.) H.-M. Rein: "Der Umschaltvorgang bei Transistor-Kippstufen – Die bistabile Kippstufe", AEÜ 19 (1965), pp. 525-535.
- 3.) H.-M. Rein, F. Weitzsch, J. Dosse: "Die Rückwärtsstromverstärkung bei Transistoren und ihr Einfluß auf die Elemente im Ersatzschaltbild von Giacioletto", AEÜ 20 (1966), pp. 73-81.
- 4.) H.-M. Rein, R. Zühlke: "Ein Beitrag zur Frequenz- und Stromabhängigkeit des Verstärkungs-Bandbreite-Produkts von legierten Flächentransistoren", AEÜ 22 (1968), pp. 66-78.
- 5.) H.-M. Rein: "Der Eingangswiderstand von Transistoren bei schnellen Schaltvorgängen", AEÜ 22 (1968), pp. 322-336.
- 6.) H.-M. Rein: "Randverdrängung und Einschnürung bei Transistoren mit zylindrischer Geometrie", Electronics Letters 4 (1968), pp. 553-554.
- 7.) H.-M. Rein, D. Straub: "SECL – Digitale integrierte Schaltungen mit besonders kleinen Schaltzeiten", Elektronik Industrie 3 (1971), pp. 26-31.
- 8.) H.-M. Rein, D. Straub: "SECL – An advanced high speed integrated circuit family", *IEEE '71 International Convention*, März 1971, New York; Digest, pp. 140-141.
- 9.) H.-M. Rein, H. Brüchmann: "Analogtransistor zur Simulation integrierter Schaltungen", Int.Elektronische Rundschau 25 (1971), pp. 227-231.
- 10.) R. Gereth, H.-M. Rein: "Problems related to advanced integrated circuits", Solid State Devices, London 1971, pp. 45-65.
- 11.) H.-M. Rein, T. Schad, R. Zühlke: "Einschnüreffekt bei Transistoren mit Streifengeometrie", Electronics Letters 7 (1971), pp. 757-758.
- 12.) H.-M. Rein: "Problem schneller integrierter Schaltungen", Frequenz 26 (1972), pp. 30-39.
- 13.) H.-M. Rein, T. Schad, R. Zühlke: "Der Einfluß des Basisbahnwiderstandes und der Ladungsträgermultiplikation auf das Ausgangskennlinienfeld von Planartransistoren", Solid-State Electronics 15 (1972), pp. 481-500.
- 14.) H.-M. Rein, H. Clauss, K. Wörner: "Subnanosekunden-Schaltkreise mit kleiner Verlustleistung und wenig Komponenten", NTZ 25 (1972), pp. 465-470.
- 15.) H.-M. Rein, W. Kosak, W. Kotte: "Schnelle integrierte Digitalschaltungen mit Schottky-Dioden", Wissenschaftliche Berichte AEG-Telefunken 45 (1972), pp. 130-141.

- 16.) H.-M. Rein, M. Zahn: "Subnanosecond pulse generator with variable pulse width using avalanche transistors", *Electronics Letters* 11 (1975), pp. 21-23.
- 17.) H.-M. Rein: "Erzeugung variabler Rechteckimpulse mit Lawinentransistoren", *AEÜ* 29 (1975), pp. 389-399.
- 18.) H.-M. Rein: "Calculation of the breakdown characteristics of bipolar transistors using a two-dimensioned model", *Solid-State Electronics* 19 (1976), pp. 145-147.
- 19.) H.-M. Rein: "Improving the large signal models of bipolar transistors by dividing the intrinsic base into two lateral sections", *Electronics Letters* 13 (1977), pp. 40-41.
- 20.) R. Ranfft, H.-M. Rein: "A simple but efficient analog computer for simulation of high-speed integrated circuits", *IEEE J. Solid-State Circuits* 12 (1977), pp. 51-58.
- 21.) H.-M. Rein, R. Ranfft: "Improved feedback ECL-gate with low delay power product for the subnanosecond region", *IEEE J. Solid-State Circuits* 12 (1977), pp. 80-82.
- 22.) H.-M. Rein: "Relationship between transient response and output characteristics of avalanche transistors", *Solid-State Electronics* 20 (1977), pp. 849-858.
- 23.) R. Ranfft, H.-M. Rein: "Analog simulation of bipolar-transistor circuits", *Simulation* (1977), pp. 75-78.
- 24.) K. Wörner, H. Clauss, H.-M. Rein, A. Kostka: "A monolithic GHz to KHz frequency divider combining ECL and I<sup>2</sup>L techniques", *ESSCIRC '78*, Amsterdam, Sept. 1977; *Dig. Techn. Papers*, pp. 73-74.
- 25.) H.-M. Rein, H. v. Rohr, P. Wennekers: "A contribution to the current gain temperature dependence of bipolar transistors", *Solid-State Electronics* 21 (1978), pp. 439-442.
- 26.) R. Ranfft, H.-M. Rein: "Optimization and comparison of various subnanosecond bipolar IC's with low power dissipation", *ESSCIRC '80*, Grenoble, Sept. 1980; *Dig. Techn. Papers*, pp. 190-192.
- 27.) H.-M. Rein, R. Ranfft: *Integrierte Bipolarschaltungen* (Bd. 13 der Reihe Halbleiter-Elektronik), 320 Seiten, 198 Abbildungen, Berlin, Heidelberg, New York, Springer 1980.
- 28.) R. Ranfft, H.-M. Rein: "High-speed bipolar logic circuits with low power consumption for LSI – a comparison", *IEEE J. Solid-State Circuits* 17 (1982), pp. 703-712.
- 29.) R. Ranfft, H.-M. Rein: "A simple optimization procedure for bipolar subnanosecond IC's", *Microelectronics Journals* 13 (1982), Nr. 4, pp. 23-28.

- 30.) J. Burkhart, B. Rall, H.-M. Rein, K. Schlüter: "A bipolar 4 x 4 crosspoint array for 140 Mbit/s data rates", *ESSCIRC'82*, Brüssel, Sept. 1982; Dig. Techn. Papers, pp. 13-16.
- 31.) H.-M. Rein: "Proper choice of the measuring frequency for determining  $f_T$ ", *Solid-State Electronics* 26 (1983), pp. 75-82.
- 32.) H.-M. Rein, D. Daniel, R. Derksen, U. Langmann, B. G. Bosch: "Design and implementation of a Gbit/s bipolar multiplexer IC", *ESSCIRC '83*, Lausanne, Sept. 1983; Dig. Techn. Papers, pp. 85-88.
- 33.) H.-M. Rein: "A simple experimental method for separation of the internal and external (peripheral) currents of bipolar transistors", *Solid-State Electronics* 27 (1984), pp. 625-632.
- 34.) H.-M. Rein, D. Daniel, R. Derksen, U. Langmann, B. G. Bosch: "A time division multiplexer IC for bit rates up to 2 Gbit/s", *IEEE J. Solid-State Circuits* 19 (1984), pp. 306-310.
- 35.) H.-M. Rein: "Entwurf einer integrierten Koppelmatrix mit geringem Leistungsverbrauch zur Vermittlung hoher Bitraten", *AEÜ* 38 (1984), pp. 345-354.
- 36.) H.-M. Rein, R. Derksen: "An integrated bipolar 4:1 time-division multiplexer for bit rates up to 3Gbit/s", *Electronics Letters* 20 (1984), pp. 546-548.
- 37.) M. Schröter, H.-M. Rein: "Two-dimensional modeling of high-speed bipolar transistors at high current densities using the Integral Charge-Control Relation", *ESSDERC'84*, Lille, Sept. 1984, Dig. Techn. Papers, pp. 334-337, veröffentlicht in *Physika* 129 B (1985), pp. 332-336.
- 38.) R. Derksen, H.-M. Rein, J. Vathke: "An integrated bipolar master-slave-D-flipflop with multiplexing capability for Gbit/s data regeneration", *Electronics Letters* 20 (1984), pp. 628-630.
- 39.) H.-M. Rein, H. Stübing, M. Schröter: "Verification of the integral charge-control relation for high-speed bipolar transistors at high current densities", *IEEE Trans. Electron Devices* 32 (1985), pp. 1070-1076.
- 40.) R. Derksen, H.-M. Rein, K. Wörner: "A monolithic 5 GHz frequency divider IC fabricated with a standard bipolar technology", *ESSCIRC '85*, Toulouse, Sept. 1985; Dig. Techn. Papers, pp. 396-400.
- 41.) R. Derksen, H.-M. Rein, K. Wörner: "Monolithic integration of a 5.3 GHz regenerative frequency divider using a standard bipolar technology", *Electronics Letters* 21 (1985), pp. 1037-1039.
- 42.) R. Reimann, H.-M. Rein: "A bipolar 4:1 time-division multiplexer IC operating up to 5.5 Gbit/s", *ISSCC '86*, Anaheim (USA), Feb. 1986, Dig. Techn. Papers, pp. 186-187.

- 43.) H.-M. Rein, R. Reimann: "A 3.8 Gb/s bipolar master-slave-D-flipflop IC as a basic element for high-speed optical communication systems", *Electronics Letters* 22 (1986), pp. 543-544.
- 44.) R. Reimann, H.-M. Rein: "A 4:1 time-division multiplexer IC for bit rates up to 6 Gb/s based on a standard bipolar technology", *IEEE J. Solid-State Circuits* 21 (1986), pp. 785-789.
- 45.) H.-M. Rein, R. Reimann: "6 Gbit/s multiplexer and regenerating demultiplexer IC's for optical transmission systems based on a standard bipolar technology", *Electronics Letters* 22 (1986), pp. 988-990.
- 46.) H.-M. Rein, R. Reimann: "Ein monolithisch integrierter bipolarer 4:1 Zeitmultiplexer für Bitraten bis 5,5 Gbit/s", *NTG-Fachtagung: Mikroelektronik für die Informationstechnik*, Sept.1986, Berlin. Published in: *NTG-Fachberichte* 96, pp. 267-272.
- 47.) R. Reimann, H.-M. Rein: "A 4 Gbit/s high-gain limiting amplifier for optical fiber receivers fabricated with a standard bipolar technology", *ISSCC '87*, New York, Feb. 1987, *Dig. Techn. Papers*, pp. 172-173, 387.
- 48.) H. Stübing, H.-M. Rein: "A compact physical large-signal model for high-speed bipolar transistors at high current densities, part I: One-dimensional model", *IEEE Trans. Electron Devices* 34 (1987), pp. 1741-1751.
- 49.) H.-M. Rein, M. Schröter: "A compact physical large-signal model for high-speed bipolar transistors at high current densities, part II: Two-dimensional model and experimental results", *IEEE Trans. Electron Devices* 34 (1987), pp. 1752-1761.
- 50.) R. Reimann, H.-M. Rein: "Bipolar high-gain limiting amplifier IC for optical fiber receivers operating up to 4 Gbit/s", *IEEE J. Solid-State Circuits* 22 (1987), pp. 504-511.
- 51.) P. Weger, R. Reimann, H.-M. Rein, L. Treitinger: "Static 7 GHz frequency divider IC based on a 2- $\mu$ m Si bipolar technology", *Electronics Letters* 23 (1987), pp. 192-193.
- 52.) H.-M. Rein: "Gbit/s silicon bipolar ICs for future optical-fibre transmission systems", *ESSCIRC'87*, Bad Soden (Germany), Sept. 1987 (*invited paper*); *Dig. Tech. Papers*, pp. 183-192.
- 53.) P. Weger, H.-M. Rein: "Speed power relation of modern bipolar technology", *ESSDERC '87*, Bologna, Sept. 1987, *Dig. Tech. Papers*.
- 54.) R. Derksen, H.-M. Rein: "7.3 GHz dynamic frequency dividers monolithic integrated in a standard bipolar technology", *IEEE Trans. Microwave Theory and Techniques* 36 (1988), pp. 537-541.
- 55.) H.-M. Rein: "Multi Gbit/s silicon bipolar ICs for future optical-fiber transmission systems", *IEEE J. Solid-State Circuits* 23 (1988), pp. 664-675.

- 56.) M. Flüge, P. T. Frederiksen, B. Enning, G. Walf, H. G. Weber, H.-M. Rein: "Wideband bipolar multiplier IC with high dynamic range for use in coherent optical receivers", *Electronics Letters* 25 (1989), pp. 44-45.
- 57.) H.-M. Rein, R. Reimann, L. Schmidt: "A 3 Gbit/s phase shifter and AGC amplifier", *ISSCC '89*, New York, Feb. 1989; *Dig. Techn. Papers*, pp. 144-145, 318.
- 58.) P. Weger, L. Treitinger, A. Wieder, H.-M. Rein: "A Si bipolar 15 GHz static frequency divider and 10 Gbit/s multiplexer", *ISSCC '89*, New York, Feb. 1989; *Dig. Techn. Papers*, pp. 222-223.
- 59.) P. Weger, L. Treitinger, J. Bieger, H.-M. Rein: "15 GHz static frequency divider IC in silicon bipolar technology", *Electronics Letters* 25 (1989), pp. 513-514.
- 60.) H.-M. Rein, M. Schröter: "Base spreading resistance of square-emitter transistors and its dependence on current-crowding", *IEEE Trans. Electron Devices* 36 (1989), pp. 770-773.
- 61.) J. Hauenschild, H.-M. Rein, P. Weger, H. Klose: "A 10 Gbit/s monolithic integrated bipolar demultiplexer for optical-fiber transmission systems fabricated in BICMOS technology", *Electronics Letters* 25 (1989), pp. 782-783.
- 62.) M. Schröter, H.-M. Rein: "Transit time of high-speed bipolar transistors in dependence on operating point, technological parameters and temperature", *IEEE 1989 Bipolar Circuits and Technology Meeting*, Minneapolis, Sept. 1989, Proc., pp. 250-253.
- 63.) J. Hauenschild, H.-M. Rein: "Time-jitter and instabilities of Gbit/s ICs caused by transmission-line interconnections", *ESSCIRC '89*, Wien, Sept. 1989; *Dig. Techn. Papers*, pp. 226-232.
- 64.) R. Reimann, H.-M. Rein: "A single-chip bipolar AGC amplifier with large dynamic range for optical-fiber receivers operating up to 3 Gbit/s", *IEEE J. Solid-State Circuits* 24 (1989), pp. 1744-1748.
- 65.) H.-M. Rein, J. Hauenschild: "On the suitability of present silicon bipolar IC technologies for optical-fiber transmission rates about and above 10 Gbit/s", *IEE Proc.-G.*, vol. 137 (1990), pp. 251-260.
- 66.) H.-M. Rein: "Silicon bipolar integrated circuits for multi-Gbit/s lightwave communications", *OFC '90 (invited paper)*, New York, *Dig. Techn. Papers*, pp. 67.
- 67.) J. Hauenschild, H.-M. Rein, L. Schmidt, K. Wörner: "Versatile silicon bipolar XOR gate for signal processing up to 8 Gbit/s", *Electronics Letters* 26 (1990), pp. 114-115.
- 68.) J. Hauenschild, H.-M. Rein: "Influence of transmission-line interconnections between Gbit/s ICs on time jitter and instabilities", *IEEE J. Solid-State Circuits* 25 (1990), pp. 763-764.
- 69.) L. Schmidt, H.-M. Rein: "A new high-speed bipolar XOR gate with absolutely symmetrical circuit configuration", *Electronics Letters* 26 (1990), pp. 430-431.

- 70.) L. Treitinger, E. Bertagnolli, K. Ehringer, M. Reisch, H. Kabza, R. Schreiter, R. Köpl, I. Weng, P. Weger, H.-M. Rein: "Silicon bipolar technology – A versatile base for high-speed communication circuits", *1990 Zurich Seminar on Digital Communications "Electronic Circuits and Systems for Communication"*, Zürich, 1990, Dig. Techn. Papers, pp. 27-38.
- 71.) H.-M. Rein: "Silicon bipolar integrated circuits for multi-Gbit/s lightwave communications", *IEEE J. Lightwave Tech.*, vol. 8 (1990), pp. 1371-1378.
- 72.) H.-M. Rein, M. Schröter: "Experimental determination of the internal base sheet resistance of bipolar transistors under forward-bias conditions", *Solid-State Electronics* 33 (1990), pp. 301-308.
- 73.) J. Hauenschild, H.-M. Rein, W. McFarland, J. Doernberg, D. Pettengill: "A 20 Gbit/s time-division multiplexer IC in silicon bipolar technology", *Electronics Letters* 26 (1990), pp.1824-1826.
- 74.) H.-M. Rein: "Integrierte Si-Schaltungen für die optische Nachrichtenübertragung bei extrem hohen Bitraten – Stand der Technik und Prognosen", (eingeladener Vortrag), *ITG-Fachtagung: Mikroelektronik für die Informationstechnik*, Berlin, Oct. 1990, Tagungsband, pp. 1-4.
- 75.) H.-M. Rein, L. Schmidt, K. Wörner: "A symmetrical analog wide-band multiplier IC operating up to 8 Gb/s", *ISSCC '91*, San Francisco, Feb. 1991, Dig. Tech. Papers, pp. 118-119, 300.
- 76.) J. Hauenschild, H.-M. Rein, W. McFarland, D. Pettengill: "A 24 Gbit/s regenerating demultiplexer IC in silicon bipolar technology", *Electronics Letters* 27 (1991), pp. 502-503.
- 77.) J. Hauenschild, H.-M. Rein, W. McFarland, D. Pettengill: "A silicon bipolar decision circuit operating up to 15 Gbit/s", *IEEE J. Solid-State Circuits* 26, (1991), pp. 1374-1376.
- 78.) J. Hauenschild, H.-M. Rein, W. McFarland, D. Pettengill: "Demonstration of the retiming capability of a silicon bipolar time-division multiplexer operating up to 24 Gbit/s", *Electronics Letters* 27 (1991), pp. 978-979.
- 79.) H.-M. Rein, J. Hauenschild, W. McFarland, D. Pettengill: "A 23 Gbit/s Si bipolar decision circuit consisting of 24 Gbit/s MUX and DEMUX IC's", *Electronics Letters* 27 (1991), pp. 974-975.
- 80.) H.-M. Rein, L. Schmidt, K. Wörner, W. Pieper: "Wide-band symmetrical analog multiplier IC for coherent optical-fiber receivers operating up to 10 Gb/s", *IEEE J. Solid-State Circuits* 26, (1991), pp. 1840-1846.
- 81.) A. Felder, P. Weger, E. Bertagnolli, J. Hauenschild, H.-M. Rein: "A Si-bipolar 23 Gbit/s multiplexer and a 15 GHz 2:1 static frequency divider", *IEEE 1991 Bipolar Circuits and Technology Meeting*, Minneapolis, Sept. 1991, Proc., pp. 31-34.

- 82.) A. Felder, P. Weger, K. Ehninger, J. Hauenschild, H.-M. Rein: "A 15 GHz static frequency divider in a 1  $\mu\text{m}$  silicon bipolar technology", *European Microwave Conference*, Stuttgart, 1991, Dig. Tech. Papers.
- 83.) R. Derksen, V. Lück, H.-M. Rein: "Stability ranges of regenerative frequency dividers with double balanced switching-type mixer", *IEEE Trans. Microwave Theory and Techniques* 39 (1991), pp. 1759-1762.
- 84.) J. Hauenschild, E. Bertagnolli, A. Felder, H.-M. Rein, H. Klose, L. Schmidt, L. Treitinger, P. Weger: "Si-Chipset with maximum data rates from 10 to 23 Gbit/s for optical communications", *Electronics Letters* 27 (1991), pp. 2383-2385.
- 85.) H.-M. Rein: "Design of a silicon bipolar laser-and line-driver IC with adjustable pulse shape and amplitude for data rates around and above 10 Gbit/s", *Frequenz* 46 (1992), H. 1-2, pp. 31-37.
- 86.) L. Schmidt, H.-M. Rein: "Continuously variable GHz phase shifter IC covering more than one frequency decade", *IEEE J. Solid-State Circuits* 27 (1992), pp. 854-862.
- 87.) H.-M. Rein, E. Bertagnolli, A. Felder, J. Hauenschild, H. Klose, L. Schmidt, L. Treitinger, P. Weger: "Ein Silizium-Chipsatz für optische Übertragungssysteme mit Datenraten von 10 bis 23 Gbit/s", *ITG Fachtagung: Mikroelektronik für die Informationstechnik*, Stuttgart, 1992, ITG Fachberichte 119, pp. 43-48.
- 88.) H.-M. Rein, J. Hauenschild, M. Möller, W. McFarland, D. Pettengill, J. Doernberg: "30 Gbit/s Si multiplexer and demultiplexer ICs in Silicon Bipolar Technologies", *Electronics Letters* 28 (1992), pp. 97-99.
- 89.) H.-M. Rein, M. Neuhäuser, H. Wernz, V. Flaßnöcker: "A 6.5 Gbit/s transimpedance preamplifier in silicon bipolar technology for optical-fibre transmission links", *Frequenz* 46 (1992), pp. 174-176.
- 90.) B. Wedding, D. Schlump, B. Franz, B. Junginger, R. Heidemann, E. Zielinski, S. Dahl-Petersen, K. Schuesler, J. Hauenschild, H.-M. Rein: "10 Gbit/s to 260000 subscribers using optical amplifier distribution network", *Proc. ICC/Supercomm '92*, Chicago, 14.-18. June 1992.
- 91.) A. Felder, J. Hauenschild, M. Kerber, H.-M. Rein: "Static silicon frequency divider for low power consumption (4 mW, 10 GHz) and high speed (160 mW, 19 GHz)", *IEEE 1992 Bipolar Circuits and Technology Meeting*, Minneapolis, Oct. 1992, Proc., pp. 159-162.
- 92.) J. Hauenschild, A. Felder, M. Kerber, H.-M. Rein, L. Schmidt: "A 22 Gb/s decision circuit and a 32 Gb/s regenerating demultiplexer IC fabricated in silicon bipolar technology", *IEEE 1992 Bipolar Circuits and Technology Meeting*, Minneapolis, Oct. 1992, Proc., pp. 151-154.
- 93.) H.-M. Rein, M. Schröter, A. Koldehoff, K. Wörner: "A semi-physical bipolar transistor model for the design of very-high-frequency analog ICs", *IEEE 1992 Bipolar Circuits and Technology Meeting*, Minneapolis, Oct. 1992, Proc., pp. 217-220.

- 94.) H.-M. Rein, E. Bertagnolli, A. Felder, L. Schmidt: "A silicon bipolar laser and line driver IC with symmetrical output pulse shape operating up to 12 Gbit/s", *Electronics Letters* 28 (1992), pp. 1295-1296.
- 95.) H.-M. Rein: "Hochgeschwindigkeits-Schaltungen in Silizium-Bipolartechnologie", *Informationstechnik* 34 (1992), pp. 209-219.
- 96.) M. Kerber, E. Bertagnolli, R. Mahnkopf, J. Popp, A. Felder, H.-M. Rein, A. Weisgerber, H. Klose: "A high performance BICMOS process featuring 40 GHz/21 ps", *IEDM '92*, San Francisco, Dec. 1992, Techn. Digest, pp. 449-452.
- 97.) T. F. Meister, R. Stengl, H. Meul, R. Weyl, P. Papan, A. Felder, H. Klose, R. Schreiter, J. Popp, H.-M. Rein, L. Treitinger: "Sub-20ps silicon BIPOLAR technology using selective epitaxial growth", *IEDM '92*, San Francisco, Dec. 1992, Techn. Digest., pp. 401-404.
- 98.) L. Treitinger, A. Felder, M. Kerber, T.F. Meister, E. Bertagnolli, P. Weger, R. Mahnkopf, S. Marksteiner, R. Kopl, R. Schreiter, J. Popp, H.-M. Rein, J. Hauenschild, L. Schmidt: "Silicon bipolar technology and circuits for optical communications at data rates > 10 Gb/s", *OFC '93*, San Francisco, Feb. 1993.
- 99.) A. Felder, R. Stengl, J. Hauenschild, H.-M. Rein, T.F. Meister: "25 to 40 Gb/s ICs in a 0.8  $\mu\text{m}$  silicon selective epitaxy bipolar technology", *ISSCC '93*, San Francisco, Feb. 1993, Dig. Techn. Papers, pp. 156-157, 281.
- 100.) A. Koldehoff, M. Schröter, H.-M. Rein: "A compact bipolar transistor model for very-high-frequency applications with special regard to narrow emitter stripes and high current densities", *Solid-State Electronics* 36 (1993), pp. 1035-1048.
- 101.) M. Neuhäuser, H.-M. Rein, H. Wernz, A. Felder: "A 13 Gbit/s Si bipolar preamplifier for optical front ends", *Electronics Letters* 29 (1993), pp. 492-493.
- 102.) A. Felder, R. Stengl, J. Hauenschild, H.-M. Rein, T.F. Meister: "25 Gbit/s decision circuit, 34Gbit/s multiplexer, and 40 Gbit/s demultiplexer IC in selective epitaxial Si bipolar technology", *Electronics Letters* 29 (1993), pp. 525-526.
- 103.) M. Schröter, M. Friedrich, H.-M. Rein: "A generalized integral charge-control relation and its application to compact models for silicon based HBTs", *IEEE Trans. Electron Devices* 40 (1993), pp. 2036-2046.
- 104.) A. Felder, R. Stengl, J. Hauenschild, H.-M. Rein, T.F. Meister: "Static frequency dividers for high operating speed (25 GHz, 170 mW) and low power consumption (16 GHz, 8 mW) in selective epitaxial Si bipolar technology", *Electronics Letters* 29 (1993), pp. 1072-1073.
- 105.) T.F. Meister, R. Stengl, A. Felder, H.-M. Rein, L. Treitinger: "Selective epitaxial bipolar technology for 25 to 40 Gb/s ICs", *ESSDERC '93*, Grenoble, France, Sept. 1993, Dig. Tech. Papers, pp. 203-210.



- 106.) E. Bertagnolli, H. Klose, R. Mahnkopf, A. Felder, M. Kerber, M. Stolz, G. Schutte, H.-M. Rein, R. Köpl: "An SOI-based high performance self-aligned bipolar technology featuring 20 ps gate-delay and a 8.6 fJ power-delay product", 1993 Symposium on VLSI Technology, Kyoto, Japan, Dig. Techn. Papers, pp. 63-64.
- 107.) L. Treitinger, A. Felder, R. Köpl, T.F. Meister, S. Pick, J. Popp, R. Schreiter, P. Weger, J. Wieland, H.-M. Rein: "Silicon technologies and integrated circuits for multi Gbit/s light-wave communication at 10–100 Gb/s", *ECOC '93*, Montreux, Sept. 1993; Dig. Techn. Papers, pp. 76-79.
- 108.) M. Möller, H.-M. Rein, H. Wernz: "A Si-bipolar AGC amplifier IC with high gain and wide dynamic range for 10 Gb/s optical-fiber receivers", *IEEE 1994 MTT-Symposium (MMWMC)*, San Diego, Ca., May 1994, Digest Techn. Papers, pp. 107-110.
- 109.) H.-M. Rein, R. Schmid, P. Weger, T. Smith, T. Herzog, R. Lachner: "A versatile Si-bipolar driver circuit with high output voltage swing for external and direct modulation of laser diodes in 10 Gb/s optical-fiber links", *IEEE J. Solid-State Circuits*, 29 (1994), pp. 1014-1021.
- 110.) M. Möller, H.-M. Rein, H. Wernz: "13 Gb/s Si-bipolar AGC amplifier with high gain and wide dynamic range for optical-fiber receivers", *IEEE J. Solid-State Circuits* 29 (1994), pp. 815-822.
- 111.) M. Neuhäuser, H.-M. Rein, H. Wernz: "Design and realization of low-noise, high-gain Si-bipolar transimpedance preamplifiers for 10 Gb/s optical-fiber links", *IEEE 1994 Bipolar Circuits and Technology Meeting*, Minneapolis, Oct. 1994, Proc., pp. 163-166.
- 112.) M. Möller, H.-M. Rein, H. Wernz: "15 Gb/s high-gain limiting amplifier fabricated in a Si-bipolar production technology", *Electronics Letters* 30 (1994), pp. 1519-1520
- 113.) H.-M. Rein, M. Friedrich: "Anomalies in the output conductance of SiGe HBTs", *IEDM '94*, San Francisco, Dec. 1994, Techn. Digest, pp. 739-742.
- 114.) M. Schröter, H.-M. Rein: "Investigation of very fast and high-current transients in digital bipolar IC's using both a new compact model and a device simulator", *IEEE J. Solid-State Circuits*, 30 (1995), pp. 551-562.
- 115.) M. Neuhäuser, M. Möller, H.-M. Rein, and H. Wernz: "Low-noise, high-transimpedance Si-bipolar AGC amplifier for 10 Gb/s optical-fiber links", *Photonics Technology Lett.* 7 (1995), pp. 549-551.
- 116.) A. Felder, M. Möller, J. Popp, J. Böde, M. Rest, H.-M. Rein, and L. Treitinger: "30 GHz static 2:1 frequency divider and 46 Gb/s multiplexer/demultiplexer ICs in a 0.6  $\mu\text{m}$  Si-bipolar technology", *1995 Symposium on VLSI Circuits*, Kyoto (Japan), June 1995, Digest Techn. Papers, pp.117-118.
- 117.) H.-M. Rein: "Design aspects of 10 to 40 Gb/s digital and analog Si-bipolar ICs", *1995 Symposium on VLSI Circuits* (invited paper), Kyoto (Japan), June 1995, Digest Techn. Papers, pp. 49-54.

- 118.) M. Pfof, H.-M. Rein, and T. Holzwarth: "Modeling the substrate effect in high-speed Si-bipolar ICs", *IEEE 1995 Bipolar Circuits and Technology Meeting*, Minneapolis, Oct. 1995, Proc. pp.182-185.
- 119.) M. Möller, H.-M. Rein, A. Felder, and J. Popp: "50 Gb/s time-division multiplexer in Si-bipolar technology", *Electronics Letters* 31 (1995), pp. 1431-1433.
- 120.) H.-M. Rein: "Very-High-Speed Si and SiGe Bipolar ICs", *ESSDERC '95 (invited paper)*, The Hague (The Netherlands), Sept. 1995, Proc. pp. 45-56.
- 121.) M. Neuhäuser, H.-M. Rein, H. Wernz: "Low-noise, high-gain Si-bipolar preamplifiers for 10 Gb/s optical-fiber links-design and realization", *IEEE J. Solid-State Circuits* 31 (1996), pp. 24-29.
- 122.) H.-M. Rein and M. Möller: "Design considerations for very-high-speed Si-bipolar ICs operating up to 50 Gb/s", *IEEE J. Solid-State Circuits* 31 (1996), pp. 1076-1090.
- 123.) A. Felder, M. Möller, J. Popp, J. Böck, and H.-M. Rein: "46 Gb/s DEMUX, 50 Gb/s MUX, and 30 GHz static frequency divider in silicon bipolar technology", *IEEE J. Solid-State Circuits* 31 (1996), pp. 481-486.
- 124.) E. Gottwald, A. Felder, H.-M. Rein et al.: "Towards a 40 Gbit/s electrical time division multiplexed optical transmission system", *Proc. ICCT '96*, Beijing, China, May 1996, pp. 60-63.
- 125.) M. Pfof, H.-M. Rein, and T. Holzwarth: "Modeling substrate effects in the design of high-speed Si-bipolar ICs", *IEEE J. Solid-State Circuits*, 31 (1996), pp. 1493-1501.
- 126.) M. Pfof and H.-M. Rein: "A proposal for modeling substrate coupling in Si-MMICs and its experimental verification up to 40 GHz", *Proc., IEEE Int. Conf. on Microelectronic Test Structures*, Monterey, CA, March 1997, pp. 52-55.
- 127.) H.-M. Rein, E. Gottwald, and T. F. Meister: "Si-bipolar – A potential candidate for high-speed electronics in 20 and 40 Gb/s TDM systems?", *Spring Topical Meetings, Ultrafast Electronics and Optoelectronics (invited paper)*, Incline Village, Nevada, USA, March 1997, *Digest Techn. Papers*, pp. 118-120, and *OSA Trends in Optics and Photonics Series*, Vol. 13: *Ultrafast Electronics and Optoelectronics*, pp. 124-128.
- 128.) M. Möller, H.-M. Rein, A. Felder, and T.F. Meister: "60 Gbit/s time-division multiplexer in SiGe-bipolar technology with special regard to mounting and measuring technique", *Electron. Lett.*, 33 (1997), pp. 679-680.
- 129.) R. Schmid, T.F. Meister, M. Neuhäuser, A. Felder, W. Bogner, M. Rest, J. Rupeter, and H.-M. Rein: "20 Gb/s transimpedance amplifier and modulator driver in SiGe-bipolar technology", *Electron. Lett.*, 33 (1997), pp. 1136-1137.

- 130.) M. Wurzer, T.F. Meister, H. Schäfer, H. Knapp, J. Böck, R. Stengl, K. Aufinger, M. Franosch, M. Rest, M. Möller, H.-M. Rein, and A. Felder: "42 GHz static frequency divider in a Si/SiGe bipolar technology", ISSCC '97, San Francisco, Feb. 1997, Dig. Tech. Papers, pp. 122-123.
- 131.) M. Pfof and H.-M. Rein: "Modeling and measurement of substrate coupling in Si-bipolar ICs up to 40 GHz", IEEE J. Solid-State Circuits, 33 (1998), pp. 582-591.
- 132.) A. Felder, M. Möller, M. Wurzer, M. Rest, T.-F. Meister, and H.-M. Rein: "60 Gbit/s regenerating demultiplexer in SiGe bipolar technology", Electron. Lett., 33 (1997), pp. 1984-1985.
- 133.) J. Müllrich, T.F. Meister, M. Rest, W. Bogner, A. Schöpflin, and H.-M. Rein: „40 Gbit/s transimpedance amplifier in SiGe bipolar technology for the receiver in optical-fiber TDM links“, Electron. Lett., 34 (1998), pp. 452-453.
- 134.) R. Schmid, T.F. Meister, M. Rest and H.-M. Rein: „23 Gbit/s SiGe modulator driver with 3.5 V single-ended output swing - design aspects and measuring results“, IEEE Workshop on MMIC Design, Packaging, and System Applications, Freiburg (Germany), Oct. 1998, Proc. pp. 87-88.
- 135.) R. Schmid, T.F. Meister, M. Rest and H.-M. Rein: „40 Gbit/s EAM driver IC in SiGe bipolar technology“, Electron. Lett., 34 (1998), pp. 1095-1097.
- 136.) H.-M. Rein: „Complete SiGe bipolar chipset for a 40 Gb/s optical-fiber TDM link“ (invited paper), Ninth Annual Workshop on Interconnections Within High Speed Digital Systems, Santa Fe, New Mexico, USA, May 1998.
- 137.) M. Möller, T.F. Meister, R. Schmid, J. Rupeter, M. Rest, A. Schöpflin and H.-M. Rein: „SiGe high-gain retiming power MUX for directly driving an EAM up to 50 Gbit/s“, Electron. Lett., 34 (1998), pp. 1782-1783.
- 138.) H.-M. Rein: „Si and SiGe bipolar ICs for 10 to 40 Gb/s optical-fiber TDM links“, (invited paper), International Journal of High Speed Electronics and Systems; Vol. 9 (1998), No 2, pp. 347-383, Special Issue on: „High Speed Electronics and Systems for Lightwave Communications“  
*as well as in "High-speed Circuits for Lightwave Communications" edited by K. C. Wang, in „Selected Topics in Electronics and Systems“, Vol. 13, edited by P. K. Tien, World Scientific Publishing, Singapore, 1999.*
- 139.) S. Wilms and H.-M. Rein: „Analytical high-current model for the transit time of SiGe HBTs“, IEEE 1998 Bipolar Circuits and Technology Meeting, Mineapolis, Sept. 1998, Proc., pp. 199-202.
- 140.) M. Friedrich and H.-M. Rein: „Analytical current-voltage relations for compact SiGe HBT models“, IEEE Trans. Electron Devices, 46 (1999), part I: pp. 1384-1393, part II: pp. 1394-1401.

- 141.) M. Schröter, H.-M. Rein, W. Rabe, R. Reimann, A. Wassener, A. Koldehoff: „Physics- and process-based bipolar transistor modeling for integrated circuit design“, *IEEE J. Solid-State Circuits*, 34 (1999), pp. 1136-1149.
- 142.) R. Schmid, T.F. Meister, M. Rest and H.-M. Rein: "SiGe driver circuit with high output amplitude operating up to 23 Gb/s", *IEEE J. Solid-State Circuits*, 34 (1999), pp. 886-891.
- 143.) M. Pfof, H.-M. Rein, W. Steiner and A. Stürmer: "Simulation of substrate coupling with special regard to shielding in high-speed Si/SiGe bipolar ICs", 29<sup>th</sup> European Microwave Conference, Munich, Germany, October 1999, Proc. Vol. 2, pp. 133-136.
- 144.) J. Müllrich, E. Müllner, J.F. Jensen, B. Stanchina, M. Kardos, H. Thurner and H.-M. Rein: "High-gain transimpedance amplifier in InP-based HBT technology for the receiver in 40 Gb/s optical-fiber TDM links", 1999 IEEE GaAs IC Symposium, Monterey, USA, October 1999, Proc. pp. 99-102.
- 145.) M. Möller, H.-M. Rein, E. Gottwald and T.F. Meister (invited paper): "SiGe bipolar ICs with data rates from 40 to 60 Gb/s for future fiber-optic systems", GAAS '99 (European Microwave Week), Munich, Germany, October 1999, Proc. pp. 344-349.
- 146.) M. Rickelt and H.-M. Rein: "Impact ionization induced instabilities in high-speed bipolar transistors and their influence on the maximum usable output voltage", *IEEE 1999 Bipolar Circuits and Technology Meeting (BCTM)*, Minneapolis, Sept. 1999, Proc. pp. 54-57.
- 147.) J. Müllrich, W. Klein, R. Khlifi, and H.-M. Rein: "A SiGe regenerative frequency divider operating up to 63 GHz", *Electron. Lett.*, 35 (1999), pp. 1730-1731.
- 148.) H.-M. Rein: „SiGe bipolar ICs for 40 Gb/s fiber-optic TDM transmission systems“, *Symposium on Opto- and Microelectronic Devices (SODC)*, Nanjing, China, April 2000.
- 149.) J. Müllrich, E. Müllner, J.F. Jensen, B. Stanchina, M. Kardos, H. Thurner and H.-M. Rein: "High-gain transimpedance amplifier in InP-based HBT technology for the receiver in 40 Gb/s optical-fiber TDM links", *IEEE J. Solid-State Circuits*, 35 (2000), pp.1260-1265.
- 150.) M. Rickelt and H.-M. Rein: „Influence of impact-ionization induced instabilities on the maximum usable output voltage of Si bipolar transistors“, *IEEE Trans. on Electron Devices*, 48 (2001), pp. 774-783.
- 151.) M. Rickelt and H.-M. Rein: „An accurate transistor model for simulating avalanche-breakdown effects in Si bipolar circuits“, *IEEE 2001 Bipolar/BiCMOS Circuits and Technology Meeting*, Minneapolis, Oct. 2001, Proc. pp. 34-37.
- 152.) W. Steiner, M. Pfof, H.-M. Rein, A. Stürmer and A. Schüppen: „Methods for measurement and simulation of weak substrate coupling in high-speed bipolar ICs“, *IEEE Trans. Microwave Theory and Techniques*, 50 (2002), pp. 1705-1713.

- 153.) H. Li, H.-M. Rein, R. Kreienkamp and W. Klein: „47 GHz VCO with low phase noise fabricated in a SiGe bipolar production“, IEEE Trans. Microwave and Wireless Component Letters, 12 (2002), pp. 79-81.
- 154.) H. Li and H.-M. Rein: „Millimeterwave VCOs with low phase noise and wide tuning range fully integrated in a SiGe bipolar production technology“, SODC 2002, Stuttgart, Germany, March 2002.
- 155.) M. Rickelt and H.-M. Rein: „A novel transistor model for simulating avalanche-breakdown effects in Si bipolar circuits“, IEEE J. Solid-State Circuits, 37 (2002), pp. 1184-1197.
- 156.) A. Schild, H.-M. Rein, J. Müllrich, L. Altenhain, J. Blank and K. Schrödinger: „Amplifier array for 12 parallel 10 Gb/s optical-fiber links fabricated in a SiGe production technology“, IEEE 2002 RFIC Symposium, Seattle, June 2002, Proc. pp. 89-92.
- 157.) A.Schild, H.-M. Rein, J. Müllrich, L. Altenhain, J. Blank and K. Schrödinger: „High-gain SiGe transimpedance amplifier array for a 12 x 10 Gb/s parallel optical-fiber link“, IEEE J. Solid-State Circuits, 38 (2003), pp. 4-12.
- 158.) H. Li and H.-M. Rein: „Millimeter-wave VCOs with wide tuning range and low phase noise, fully intergrated in a SiGe production technology“, IEEE J. Solid-State Circuits, 38 (2003), pp. 184-191.
- 159.) W. Steiner, H.-M. Rein, J. Müllrich and A. Schild: „Reducing substrate coupling in 10 to 40 Gbit/s high-gain broadband amplifiers“, ESSCIRC 2002, Firenze, Italy, September 2002, pp. 299-302.
- 160.) H. Li, H.-M. Rein, R.-E. Makon and M. Schwerd: „Wide-band VCOs in SiGe production technology operating up to about 70 GHz“, IEEE Microwave and Wireless Comp. Letters, 13 (2003), pp. 425-427.
- 161.) H. Li, H.-M. Rein and M. Schwerd: „SiGe VCOs operating up to 88 GHz, also suited for automotive radar sensors“, Electron. Lett., 39 (2003), pp. 1326-1327.
- 162.) H. Li, H.-M. Rein and T. Suttorp: „Design of W-Band VCOs with high output power for potential application in 77 GHz automotive radar systems“, 2003 GaAs IC Symposium, San Diego, USA, November 2003, pp. 263-266.
- 163.) H. Li, H.-M. Rein, T. Suttorp and J. Böck: „Fully integrated SiGe VCOs with powerful output buffer for 77 GHz automotive radar systems and for applications around 100 GHz“, IEEE J.Solid-State Citcuits, 39 (2004), pp. 1650-1658.
- 164.) W. Steiner, H.-M. Rein and J. Berntgen: “Experimental verification of substrate coupling in a high-gain 30 Gb/s SiGe amplifier”, IEEE 2004 Bipolar/BiCMOS Circuits and Technology Meeting, Sept. 2004, Proc. pp. 273-276.

- 165.) D. Kuchta, Y. Kwark, C. Schuster, C. Baks, C. Haymes, J. Schaub, P. Pepeljugoski, L. Shan, R. John, D. Kucharski, D. Rogers, M. Ritter, J. Jewell, L. Graham, K. Schrödinger, A. Schild, H.-M. Rein: "120 Gb/s VCSEL-based parallel optical link and custom 120 Gb/s testing station"; Proc. Electronic Components and Technology Conference; Las Vegas, NV, Juni 2004, pp. 1003-1011.
- 166.) D. Kuchta, Y. Kwark, C. Schuster, C. Baks, C. Haymes, J. Schau, L. Shan, R. John, D. Kucharski, D. Rogers, M. Ritter, J. Jewell, L. Graham, K. Schrödinger, A. Schild, H.-M. Rein: "120 Gb/s VCSEL-based parallel optical interconnect and custom 120 Gb/s testing station", IEEE J. Lightwave Technology, 22 (2004), pp. 2200-2212.
- 167.) W. Steiner, H.-M. Rein, J. Berntgen: "Substrate coupling in a high-gain 30 Gb/s SiGe amplifier – modeling, suppression, and measurement", IEEE J. Solid-State Circuits, 40 (2005), pp. 2035-2045.
- 168.) H.-P. Forstner, H. Knapp, C. Gamsjaeger, H.-M. Rein, J. Boeck, T. Meister, K. Aufinger: "A 19GHz VCO downconverter MMIC for 77GHz automotive radar frontends in a SiGe bipolar production technology", IEEE European Radar Conference, Munich, 2007
- 169.) N. Pohl, H.-M. Rein, T. Musch, K. Aufinger, J. Hausner: "An 80GHz SiGe bipolar VCO with wide tuning range using two simultaneously tuned varactor pairs", 2008 IEEE CSIC Symposium, Monterey, USA, Oct. 2008, Dig. pp. 193-196.
- 170.) N. Pohl, H.-M. Rein, T. Musch, K. Aufinger, J. Hausner: "SiGe bipolar VCO with ultra-wide tuning range at 80GHz center frequency", submitted to IEEE J. Solid-State Circuits